

RLED 2.0 Light Dimmer

Features

- Two independent channels
- Simple calibration process enables support for almost all LED bulbs on the market
- Maximum output current: 1200 VA (230/115 VAC)
- Auto/Manual/Off mode for each channel

Benefits

- Lights can be dimmed to extremely low levels of light intensity
- High level of stability extends bulb life
- Simple calibration process enables support for a wide variety of bulbs
- Automatic and manual brightness control provides lighting only when required
- Key hole mounting simplifies installation
- Rugged terminals and water tight seals for power cables meet rigorous poultry house conditions

RLED 2.0

Light Dimmer for Energy Saving Lamps

RLED 2.0 provides simple, effective control over the majority of LED lighting systems used in the poultry industry. Along with the RLED 2.0's advanced electronic circuits, the Light Dimmer's software package provides superior performance and functionality, enabling high caliber, stable dimming capability. The RLED 2.0 can be managed directly by a poultry house controller via 0-10 volt analog output or communication line.



Rled 2.0



Up to 10 independent channels

in Platinum Layers mode. Other modes support up to 4 channels.

Day	From Time	Light Dimmer										
		1	2	3	4	5	6	7	8	9	10	
1	05:00	100%	100%	100%	100%	100%	100%	100%	100%	100%	100%	
1	00:00	10%	10%	10%	10%	10%	10%	10%	10%	10%	10%	
7	06:00	100%	100%	100%	100%	100%	100%	100%	100%	100%	100%	
7	00:00	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	
14	07:00	80%	80%	80%	80%	80%	80%	80%	80%	80%	80%	
14	00:00	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	



Platinum Touch



556 Industrial Way West
Eatontown, NJ 07724

732-363-2333
Info@DiversifiedAg.com
DiversifiedAg.com

