



## GAS-FIRED TWO-STAGE FORCED AIR HEATER



Electronic Two-stage

NG to LPG with only one gas valve

### GAS-FIRED TWO-STAGE FORCED AIR HEATER

- Rate 250,000/160,000 BTU/H
- Flexible interior and exterior installations options
- High temperature protection
- Enclosed motor for safe and dependable operation
- Switches between stages with a two stage thermostat
- Corrosion resistant galvanized steel or stainless steel housing with internal aluminized steel components
- Control module enclosed in a dusttight, water-resistant box
- 3-year limited warranty on burner and controls

Corrosion resistant components

The SRP Forced Air Heater provides consistent and reliable heat for a variety of poultry, fowl and pig producing environments. The direct-fired design delivers exceptional efficiency with either natural gas or propane. It will provide years of heavy-duty performance even in the harshest environments.







Superior Radiant Products is an industry leader in the design and manufacture of superior heating equipment for agricultural, commercial and industrial global markets since 1995.

# SPECIFICATIONS SRP GAS-FIRED FORCED AIR TWO-STAGE HEATER

CONFIGURATION						
Models	AA250 Galvanized steel - AA250S S/S					
Input Rate	250,000/160,000 BTU/H					
Weight	115 lbs					
Minimum Supply	Natural Gas	Propane				
	5" W.C.	11" W.C.				
Ignition	Direct Spark Ignition (DSI)					
Electrical Supply	120 Vac / 60 Hz / 1 PH / 4 Amp					

Superior gas valve design, manifold orifice assembly

- Easy to maintain
- Fault-proof orifice for easy burner alignment


Fuel conversion kit BK010: NG to LPG with one gas valve

Easily switches between stages with a two-stage thermostat. It can also run with a single-stage thermostat either on low or high fire

() F	) TI	$\mathbf{O}$ N	<b>JAL</b>	FΟι	JIPM	IFNT
		•				

- Hanging kit
- Thermostat
- Gas flex connector
- Shut off valve
- Conversion kit **BK010**: NG/LPG with one gas valve

CLEARANCE TO COMBUSTIBLES						
Outlet	Below	Side/Front/Rear	Above			
Α	В	С	D			
72"	12"	12"	12"			



### **DIMENSIONS**

















All models are CSA approved

