



DIVERSIFIED



SUPERIOR RADIANT PRODUCTS

GAS-FIRED TWO-STAGE FORCED AIR HEATER



**Electronic
Two-stage**


**NG to LPG
with only one
gas valve**

**Corrosion
resistant
components**

GAS-FIRED TWO-STAGE FORCED AIR HEATER

- Rate 250,000/160,000 BTU/H
- Flexible interior and exterior installations options
- High temperature protection
- Enclosed motor for safe and dependable operation
- Switches between stages with a two stage thermostat
- Corrosion resistant galvanized steel housing with internal aluminized steel components
- Control module enclosed in a dust-tight, water-resistant box
- 3-year limited warranty on burner and controls

The **SRP Forced Air Heater** provides consistent and reliable heat for a variety of poultry, fowl and pig producing environments. The direct-fired design delivers exceptional efficiency with either natural gas or propane. It will provide years of heavy-duty performance even in the harshest environments.



Superior Radiant Products is an industry leader in the design and manufacture of superior heating equipment for agricultural, commercial and industrial global markets since 1995.

SAVING ENERGY FOR FUTURE GENERATIONS
WWW.SUPERIORRADIANT.COM

SPECIFICATIONS

SRP GAS-FIRED FORCED AIR TWO-STAGE HEATER

CONFIGURATION		
Model	AA250	
Input Rate	250,000/160,000 BTU/H	
Weight	115 lbs	
Minimum Supply	Natural Gas 5" W.C.	Propane 11" W.C.
Ignition	Direct Spark Ignition (DSI)	
Electrical Supply	120 Vac / 60 Hz / 1 PH / 4 Amp	
Superior gas valve design, manifold orifice assembly		
<ul style="list-style-type: none"> • Easy to maintain • Fault-proof orifice for easy burner alignment 		
Fuel Conversion Kit BK010 : NG to LPG with one gas valve		
Easily switches between stages with a two-stage thermostat. It can also run with a single-stage thermostat either on low or high fire		

OPTIONAL EQUIPMENT
<ul style="list-style-type: none"> • Hanging kit • Thermostat • Gas flex connector • Shut off valve • Fuel Conversion Kit BK010: NG to LPG with one gas valve

CLEARANCE TO COMBUSTIBLES	
Rear	12"
Sides	12"
Top to ceiling	12"
Blower outlet	72"

Complies with:
 CAN-1-2-20-M85
 IAS U.S. No. 8-94 (Draft No. 2)



DIMENSIONS



DIVERSIFIED

Diversified Agriculture LLC
 556 Industrial Way West
 Eatontown, NJ 07724

1-800-348-6663
 info@diversifiedag.com
 DiversifiedAg.com